



Manufactured by:
Eclectic Products, Inc.
Pineville, LA 71361

Made in the USA

800.767.4667 - Technical Services

www.eclecticproducts.com

www.famowood.com

TECHNICAL DATA SHEET

***Famowood® Solvent-Based
Wood Filler***

PRODUCT DESCRIPTION

FAMOWOOD® SOLVENT-BASED WOOD FILLER has been the first choice of woodworking professionals for more than 50 years. Whether you're masking small or large defects, **FAMOWOOD®** can be used inside or outside and takes stains and paint evenly, making it ideal for any custom project. **FAMOWOOD®** spreads evenly into cracks and holes without shrinking, crumbling or cracking. In addition, **FAMOWOOD®** requires very little sanding to achieve a desired finished look.

PRODUCT CHARACTERISTICS and BENEFITS

High solid content	Saw, drill, sand, plane and nail, just like real wood
Fast dry time	Can be indoors and outdoors
Easy application	Spreads evenly into cracks and holes without crumbling or cracking
Superior strength	Hard finish with little or no shrinkage
Quality finish	Takes stains and paints evenly with minimal sanding

PHYSICAL PROPERTIES

Color(s)	Alder, Ash, Birch, Cedar, Cherry, Fir, Mahogany, Maple, Natural, Oak, Pine, Red Oak, Teak, Tupelo, Walnut, White, White Pine, White Glaze (18 colors)
Density	11.5 - 12.5 lbs/gal
Solids	76% ± 1.0% (by weight)
Vehicle	Nitrocellulos Lacquer
Storage	Store between 45°F (7°C) and 85°F (29°C)
Freeze/thaw stability	None; do not freeze
Shelf life	1 year

DIRECTIONS FOR USE and APPLICATION NOTES

Please read all directions before using. Always test a small area before full use.

- Step 1** For best adhesion, cracks or defects should be clean and dry.
- Step 2** Press firmly into defect by hand, or with putty knife.
- Step 3** Lower temperatures require longer drying periods.
- Step 4** When dry, sand flush with surrounding surfaces.
- Step 5** Surfaces may be painted, varnished, lacquered, waxed, or shellacked.
- Step 6** Clean up FAMOWOOD® Solvent-Based Wood Filler using FAMOWOOD® Solvent.
- Step 7** Close container after each use.

For technical assistance, call 800.767.4667.

- Use in well-ventilated area only. Avoid breathing vapors. Wear gloves and appropriate skin protection.
- FAMOWOOD® Solvent-Based Wood Filler can be drilled, nailed, planed, or sawed like ordinary wood.
- Use FAMOWOOD® Solvent to restore wood filler to its original consistency.

TECHNICAL DATA SHEET

HAZARDS

This product is a flammable solid. Before working with this product, read and become familiar with information concerning hazards, proper use and handling. To request an MSDS, please send an Email to msds@eclecticproducts.com or call 800.333.9826.

LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use and service for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products, Inc. P.O. Box 4450, Pineville, LA 71360 or call 800.767.4667. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.

WOOD FILLER COMPARISON RESULTS

(RATINGS: A - Excellent, B - Good, C - Fair, D - Poor)

	<u>FAMOWOOD® WOOD FILLER</u>	<u>DAP WOOD DOUGH</u>	<u>DARWORTH FIX WOOD PATCH</u>	<u>BOYLE-MIDWAY PLASTIC WOOD</u>
APPLICATION ease of handling, stays in void, doesn't roll up on knife, consistency	B	B	A	B
DRY TIME in minutes, same mils	13	54	16	34
SANDABILITY tested with 3m Tri Mite open coat 220 grit 150 handsanding	A	B	B	B
APPEARANCE looks like wood, blends with oils, takes stains	A	C	B	B
SHRINKAGE allowance offsetting, evaporation, solids content	A	C	B	C
ADHESION adheres to substrate-wood, metal	A	B	A	C
DURABILITY sawed, drilled, planed, nailed	A	B	A	B